

CT Generators

32/42/50kW 16-64 Slice
50/80kW 16-128 Slice
110kW 64-264 Slice

technical specifications





Innovative CT Generator Solutions...



32/42/50kW 16-64 slice single chassis "compact" CT generator



50kW/80kW 16-128 slice "performance" CT generator with grid/Z deflection

Spellman High Voltage—setting the standard for CT generator design and manufacture

- **Rotational CT up to 240rpm**
- **Designed to drive all industry standard CT tubes**
- **Digital interface allows for ease of integration**
- **Subsystem availability with all industry available X-Ray tube suppliers**

CT Generator Options

- Fast rise time
- Grid: cut off, beam deflection and focal spot adjustment
- Dual energy

If you are planning a new CT product, you can count on Spellman to have the generator platform you need. From value to premium segment solutions, our CT generators are field proven to provide the highest reliability and image quality.

Spellman High Voltage has been designing and manufacturing CT generators for OEM customers for over three decades. We have unrivaled experience being the first provider of a CT generator used in a commercially available continuous rotating CT scanner in 1985. Since then Spellman has enhanced performance and developed new CT generators year after year, setting the standard for CT generator technology.

Innovation & Quality:

With over 70 years of high voltage innovation, world-class ISO certified production facilities and global support network, Spellman can meet the needs of discriminating global OEM's system manufacturers

Compliance and Safety:

Safety and Regulatory Agency approvals such as: UL, CSA, and IEC can be provided. In addition, Spellman is authorized to conduct UL sanctioned testing

Support and Service:

Our globally situated technical support centers are strategically located to provide rapid local response to customer needs

OEM Customization:

The standard CT Generator platforms shown here are just the starting point. Spellman can provide a customized CT generator for your specific OEM requirement. Spellman's CT generators can power industry standard CT X-Ray tubes from manufacturers such as Dunlee, Varex and Toshiba.



Spellman High Voltage – Global Superiority in CT Generators

from 32kW to 110kW



110kW 64-264 slice "premier" CT generator for state of the art CT systems

MODEL	32/42/50kW Compact CT Generator	50/80kW CT Generator	110 kW CT Generator
Model Designation	CCT70PN32 CCT70PN42 CCT70PN50	CT70PN50 CT70PN80	CT140N110
Input Power	400Vac, 3Ø, +15%/-20%, 50/60Hz		
Auxiliary Input Power	220/230Vac, 1Ø +15%/-10%, 50/60Hz	220/230Vac, 1Ø +15%/-10%, 50/60Hz	Not required
kV Output Range	60kV - 140kV (bipolar, 30kV – 70kV)	60kV - 140kV (bipolar, 30kV – 70kV)	60kV to 140kV Anode grounded
kV Output Accuracy	±0.5% of setting		
mA Output Range	10mA – 300mA / 32kW maximum 10mA – 350mA / 42kW maximum 10mA – 360mA / 50kW maximum	10mA – 420mA / 50kW maximum 10mA – 667mA / 80kW maximum	6mA to 900mA, 110kW maximum
mA Regulation/Accuracy	2% or 2mA or which is larger for 20mA -350mA	2% or 1mA or which is larger for 20mA -420mA	2% or 1mA or which is larger for 20mA -900mA
Filament Output	2 outputs: 15Vac @ 0-6A up to 8A available	1 output: 15Vac @ 0-6A, up to 15A available 2 filament/no grid configuration available	2 outputs: 10Vac @ 0-8A,
Filament Accuracy	±5% of setting	±5% of setting	±2% from 25% to 75%, 5% above
Filament Repeatability	±0.2%		
Starter	HSS configured to match X-Ray tube used		
Interface	Custom serial interface		
Rotation	Up to 120 rpm	Up to 120 rpm	Up to 240 rpm
Configuration	Single chassis	Two chassis	Four chassis
Grid Option	Dual grid/single filament, 0-4kV @ 0-4kHz (separate assembly)	Dual grid/single filament, 0-4kV @ 0-4kHz (built-in)	n/a
Magnetic Z Deflection Option	n/a	Ground based single channel beam steering	n/a

Please consult factory regarding product configuration availability and regulatory requirements for specific markets

Let us simplify your production process by providing a turn-key generator-tube subsystem

- All components undergo quality control and verification inspection by Spellman engineers
- All components are tested individually
- Components are then integrated and calibrated as part of a system
- Shipped as one complete subsystem to customer for installation
- One point of contact for all product support needs



Spellman USA and Corporate HQ

475 Wireless Blvd.
Hauppauge, NY 11788
United States
tel: +1-631-630-3000
fax: +1-631-435-1620
email: sales@spellmanhv.com

Spellman Valhalla NY USA

One Commerce Park
Valhalla, NY 10595
United States
tel: +1-914-686-3600
fax: +1-914-686-5424

Spellman UK

Broomers Hill Park #14, Broomers Hill
Pulborough, West Sussex,
United Kingdom RH20 2RY
tel: +44 (0) 1798 877000
fax: +44 (0) 1798 872479

Spellman Japan

4-3-1 Kamitoda,
Toda-shi, Saitama-ken,
Japan 335-0022
tel: +81 (0) 48-447-6535
fax: +81 (0) 48-445-7280

Spellman China

Spellman High Voltage Electronics (SIP) Co Ltd.
Block D, No.16 SuTong Road,
Suzhou Industrial Park 215021 China
tel: +(86)-512-69006010
fax: +(86)-512-67630030

Spellman High Voltage Korea Co.,Ltd.

#B-720, BRC Smart Valley,
Song Do Mirae-ro 30,
Yeonsu-Gu, Incheon, Korea 406-081
tel: +82-32-719-2300
fax: +82-32-720-4300

Spellman de Mexico – Plant 2

Avenida Pedregal # 2 Esquina
Avenida Chapultepec
Parque Industrial FINSA Oriente
Matamoros, Tamps., Mexico 87340
tel. +52 868 150-1200

Spellman de Mexico – Plant 3

Avenida Chapultepec # 101 Esquina
Avenida Horizonte
Parque Industrial FINSA Oriente
Matamoros, Tamps., Mexico 87340
tel. +52 868 150-1200

Spellman High Voltage GmbH

Josef-Baumann-Straße 23
44805 Bochum
Germany
tel: +49 (0) 234 87906-0
fax: +49 (0) 234 87906-11

